## NSN 5305-01-254-2560

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-254-2560 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.252 inches and 0.364 inches **Fastener Length:** Between 0.699 inches and 0.729 inches **Head Style:** Hexagon **Head Height:** Between 0.172 inches and 0.203 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.158 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 140000 pounds per square inch Hardness Rating: 24.0 rockwell c and 35.0 rockwell c Minimum Yield Strength: 85000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** 

Shelf Life:

**Thread Series Designator:** 

Qq-p-35 federal specification single treatment response

N/a

Unjf

## NSN 5305-01-254-2560

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0