## NSN 5305-01-255-3059

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-255-3059 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.180 inches **Fastener Length:** Between 0.544 inches and 0.575 inches **Head Height:** 0.060 inches Width Between Flats: Between 0.203 inches and 0.235 inches First Diameter From Head: Between 0.122 inches and 0.124 inches **Second Diameter From Head:** Between 0.085 inches and 0.095 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.069 inches and 0.079 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.290 inches and 0.310 inches **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel **Material Specification:** Aisi b112 assn standard single material response or aisi c1215 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Mil-p-416 type 11, class 3 military specification single treatment response Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A003b0

## NSN 5305-01-255-3059

Externally Relieved Body Screw - Page 2 of 2



Mil-std (military Standard):

Mil-p-416 spec.