NSN 5305-01-256-5199

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-256-5199 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.542 inches and 0.609 inches **Fastener Length:** Between 0.604 inches and 0.609 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Criticality Code Justification:** Supp **Special Features:** Supplemental coating with chromate optional no min. Thickness required, but 100 percent coverage is required Material: Steel **Nuclear Hardness Critical Feature:** Hardened **Surface Treatment:** Cadmium **Surface Treatment Specification:** Mil-std-865 military standard single treatment response **Supplementary Features:** Item has other critical features such as tolerance, fit restrictions or application as well as being nuclear hard **Thread Series Designator:** Unc

N/a

Shelf Life:

NSN 5305-01-256-5199

Socket Head Cap Screw - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-std-865 spec.