NSN 5305-01-256-5779

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-256-5779 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.265 inches and 0.297 inches **Fastener Length:** 0.719 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.312 inches **Head Height:** 0.188 inches **First Diameter From Head:** Between 0.085 inches and 0.105 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.422 inches and 0.454 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** Between 77.0 degrees and 87.0 degrees Material: Steel **Material Specification:** Mil-w-52263c military specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072 e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-01-256-5779

Externally Relieved Body Screw - Page 2 of 2



--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-w-52263c spec.