

View Online at <https://aerobasegroup.com/nsn/5305-01-256-5793>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.406 inches

Fastener Length:

Between 0.641 inches and 0.687 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.376 inches and 0.385 inches

Grip Diameter:

0.1886 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole

Single Shear Strength:

2620 pounds per square inch

Internal Drive Style:

Cross recess type ii

Thread Diameter:

0.190 inches

Grip Length:

0.250 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

100.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.517 inches first hole

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-8844 military specification 2nd material response or ams6414 assn standard 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, typ ii, cls 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas333 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.