

View Online at <https://aerobasegroup.com/nsn/5305-01-256-5800>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.323 inches

Fastener Length:

Between 0.620 inches and 0.650 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.266 inches and 0.303 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Internal Drive Style:

Tri-wing recess

Thread Diameter:

0.190 inches

Grip Length:

Between 0.302 inches and 0.322 inches

Thready Qty Per Inch (tpi):

32

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000, uns g43406 military specification 1st material response or ams 6322 assn standard 2nd material response or mil-s-6049, uns g87400 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Supplementary Features:

Tri-wing recess no. Nas4000-4

Thread Series Designator:

Unjf

Specification Data:

80205-nas4703 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.