NSN 5305-01-259-1172

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-259-1172 **Thread Direction:** Right-hand Thread Length: 14.0 millimeters **Fastener Length:** 50.0 millimeters **Head Style:** Pan no. 2 **Head Diameter:** 9.0 millimeters **Head Height:** 5.0 millimeters Point Length: 1.6 millimeters **First Diameter From Head:** 3.8 millimeters **Second Diameter From Head:** 5.0 millimeters Distance From Largest Bearing Surface Of Head To End Of First Diameter: 36.0 millimeters Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 50.0 millimeters **Point Style:** Flat **Internal Drive Style:** Hexagon **Thread Diameter:** 5.0 millimeters Width Across Flats: 4.0 millimeters **Nonstandard Thread Pitch Diameter:** +4.4200/+4.4800 inches Min. Tensile Strength (psi): 125000 pounds per square inch **Thread Pitch In Millimeters:** 0.80 **External Thread Tolerance Class:** 4g6g **Externally Relieved Body Diameter Quantity:**

Point Chamfer Angle:

90.0 degrees

NSN 5305-01-259-1172

Externally Relieved Body Screw - Page 2 of 2



Material:
Stainless steel
Surface Treatment:
Passivate
Thread Series Designator:
Iso s
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0