

View Online at <https://aerobasegroup.com/nsn/5305-01-259-1191>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.238 inches

Fastener Length:

Between 1.598 inches and 1.628 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.206 inches and 0.210 inches

Head Height:

Between 0.060 inches and 0.069 inches

Grip Diameter:

Between 0.110 inches and 0.112 inches

Internal Drive Style:

Tri-wing recess

Thread Diameter:

0.112 inches

Grip Length:

Between 1.365 inches and 1.385 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

40

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Surface Finish:

32.0 microinches threads

Material:

Steel comp e4340 or steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000, g43606 military specification 1st material response or mil-s-5000, g43400 military specification 2nd material response or mil-s-6049 military specification 3rd material response or ams 6322 assn standard 3rd material response or sae j404, g87400 assn standard 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Supplementary Features:

Tri-wing recess no. Nas4000-2

Thread Series Designator:

Unjc

Specification Data:

80205-nas5000 professional/industrial association standard

Specification Or Standard:

3 class and b type and 3 table and 0.112-40 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.