

View Online at <https://aerobasegroup.com/nsn/5305-01-259-1198>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.370 inches

Fastener Length:

Between 1.355 inches and 1.385 inches

Head Style:

Dished hexagon

Head Height:

Between 0.125 inches and 0.140 inches

Width Between Flats:

Between 0.429 inches and 0.439 inches

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

Single Shear Strength:

95000 pounds per square inch

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.250 inches

Grip Length:

Between 0.990 inches and 1.000 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, typ ii, cls 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas6404 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0