NSN 5305-01-259-1198

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-259-1198

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.370 inches
Fastener Length:
Between 1.355 inches and 1.385 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.429 inches and 0.439 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Single Shear Strength:
95000 pounds per square inch
Internal Drive Style:
W/o internal drive
Thread Diameter:
0.250 inches
Grip Length:
Between 0.990 inches and 1.000 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, typ ii, cls 2 federal specification all treatment responses
Thread Series Designator:
Unjf
Specification Data:
80205-nas6404 professional/industrial association standard
Shelf Life:
N/a

NSN 5305-01-259-1198

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0