## NSN 5305-01-259-3548

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-259-3548

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.370 inches
Fastener Length:
Between 1.605 inches and 1.635 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.473 inches and 0.492 inches
Head Height:
Between 0.133 inches and 0.150 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
Tri-wing recess
Thread Diameter:
0.2500 inches
Grip Length:
Between 1.240 inches and 1.260 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Material:
Iron alloy 660
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl3 federal specification 1st treatment response
Thread Series Designator:
Unif
Specification Data:
80205-nas5004 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-01-259-3548

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

