NSN 5305-01-259-4055

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-259-4055 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.202 inches and 0.212 inches **Fastener Length:** 0.375 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.307 inches and 0.317 inches **Head Height:** Between 0.296 inches and 0.328 inches Point Length: 0.094 inches **Point Diameter:** Between 0.079 inches and 0.095 inches **First Diameter From Head:** Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.069 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** Between 85.0 degrees and 95.0 degrees **Special Features:** Straight knurl Material: Steel comp 203ez or steel comp 303 or steel comp 303 plus x or steel comp 303cu or steel comp 303ma or steel comp 303pb or steel comp 416 or steel comp 416 plus x or steel comp 416se or steel comp 430f or steel comp 430fse **Surface Treatment: Passivate**

Qq-p-35 federal specification single treatment response

Surface Treatment Specification:

NSN 5305-01-259-4055

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0