NSN 5305-01-259-4062

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-259-4062

Thread Class:
3a
Sa Thread Direction:
Right-hand
Thread Length: Between 0.444 inches and 0.494 inches
Fastener Length:
Between 1.829 inches and 1.859 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.497 inches and 0.507 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Shank Unthreaded Hole Diameter:
0.076 inches first hole and 0.081 inches first hole
Internal Drive Style:
High-torque Thread Diameter:
0.250 inches
Grip Length:
Between 1.365 inches and 1.385 inches
Thready Qty Per Inch (tpi): 28
Min. Tensile Strength (psi):
125000 pounds per square inch Countersink Angle:
-
Between 99.0 degrees and 101.0 degrees
Distance From Head Largest Bearing Surface To Shank Hole Center: 1.708 inches first hole and 1.748 inches first hole
Product Name:
Navy special project Material:
Steel comp xm-13
Material Specification:
Ams5629 assn standard single material response Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:

Unjf

NSN 5305-01-259-4062

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

