

View Online at <https://aerobasegroup.com/nsn/5305-01-259-7748>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.900 inches and 2.250 inches

**Fastener Length:**

Between 2.150 inches and 2.250 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 1.479 inches and 1.500 inches

**Head Height:**

Between 0.988 inches and 1.000 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

1.000 inches

**Width Across Flats:**

Between 0.750 inches and 0.757 inches

**Thready Qty Per Inch (tpi):**

8

**Min. Tensile Strength (psi):**

70000 pounds per square inch

**Hardness Rating:**

74.0 rockwell c

**Minimum Yield Strength:**

26000 pounds per square inch

**Material:**

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp xm-7 or steel comp 384

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unrc

**Specification Data:**

80205-nas1352 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0