## NSN 5305-01-259-9762

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-259-9762

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.403 inches
Fastener Length:
Between 0.585 inches and 0.605 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.477 inches and 0.492 inches
Head Height:
Between 0.140 inches and 0.150 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Grip Length:
Between 0.177 inches and 0.197 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5735 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1578 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-01-259-9762

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0