NSN 5305-01-259-9763

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-259-9763

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.363 inches |
| Fastener Length: |
| Between 0.660 inches and 0.690 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.3390 inches and 0.3813 inches |
| Grip Diameter: |
| Between 0.1885 inches and 0.1895 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.302 inches and 0.322 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single |
| material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416 ty2 cl2 federal specification all treatment responses |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas1580 professional/industrial association standard |
| Shelf Life: |
| N/a |

__

Unit Of Measure:

NSN 5305-01-259-9763

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0