## NSN 5305-01-259-9763

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-259-9763

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.363 inches
Fastener Length:
Between 0.660 inches and 0.690 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.3390 inches and 0.3813 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single
material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification all treatment responses
Thread Series Designator:
Unjf
Specification Data:
80205-nas1580 professional/industrial association standard
Shelf Life:
N/a

\_\_

**Unit Of Measure:** 

## NSN 5305-01-259-9763

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0