NSN 5305-01-260-0438

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-260-0438

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.313 inches and 0.363 inches |
| Fastener Length: |
| Between 0.761 inches and 0.791 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.339 inches and 0.381 inches |
| Grip Diameter: |
| Between 0.1890 inches and 0.1895 inches |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.428 inches and 0.448 inches |
| Features Provided: |
| Cetyl alcohol lubricant |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 63.0 microinches bearing surface of head |
| Product Name: |
| Navy special project |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas1790 professional/industrial association standard |
| Shelf Life: |
| N/a |

N/a

NSN 5305-01-260-0438

Close Tolerance Screw - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A003b0