NSN 5305-01-260-4923

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-260-4923 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.359 inches and 0.391 inches **Fastener Length:** Between 1.172 inches and 1.202 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.557 inches and 0.567 inches **Head Height:** Between 0.234 inches and 0.266 inches **First Diameter From Head:** Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.802 inches and 0.822 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 or steel comp 303se **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-260-4923

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0