# NSN 5305-01-260-5867

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-260-5867



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.327 inches and 0.420 inches

# Fastener Length:

Between 0.469 inches and 0.500 inches

#### **Head Style:**

Flat countersunk

#### Head Diameter:

Between 0.322 inches and 0.385 inches

#### Internal Drive Style:

Torque set

#### **Thread Diameter:**

0.190 inches

#### Thready Qty Per Inch (tpi):

32

# Min. Tensile Strength (psi):

160000 pounds per square inch

#### Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### **Screw Material:**

Iron alloy 660

#### **Screw Material Specification:**

Ams5737 assn standard single material response

#### Screw Surface Treatment:

Passivate

# Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

# **Specification Data:**

80205-nas1102 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

# **NSN 5305-01-260-5867** Machine Screw - Page 2 of 2

Fiig: A500d0

