## NSN 5305-01-260-7688

Machine Screw - Page 1 of 1

Fiig: A500d0



View Online at https://aerobasegroup.com/nsn/5305-01-260-7688 **Thread Class:** 2a **Thread Direction:** Right-hand **Fastener Length:** Between 0.167 inches and 0.187 inches **Head Style:** Pan **Head Diameter:** Between 0.104 inches and 0.116 inches **Head Height:** Between 0.036 inches and 0.044 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.060 inches Thready Qty Per Inch (tpi): 80 **Screw Material:** Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 385 **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No