

View Online at <https://aerobasegroup.com/nsn/5305-01-260-7689>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.100 inches and 0.120 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 0.104 inches and 0.116 inches

**Head Height:**

Between 0.031 inches and 0.039 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.060 inches

**Thready Qty Per Inch (tpi):**

80

**Screw Material:**

Copper alloy 268 or copper alloy 260 or copper alloy 230 or copper alloy 377 or copper alloy 360 or copper alloy 353 or copper alloy 270 or copper alloy 274 or copper alloy 462 or copper alloy 464 or copper alloy 482 or copper alloy 485 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 757 or copper alloy 764 or copper alloy 770 or copper alloy 240 or copper alloy 342

**Screw Surface Treatment:**

Oxide

**Screw Surface Treatment Specification:**

Mil-f-495 military specification single treatment response

**Color:**

Black

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-f-495 spec.