NSN 5305-01-260-8937

Close Tolerance Screw - Page 1 of 2



assn standard single

View Online at https://aerobasegroup.com/nsn/5305-01-260-8937

Thread C	lass:
3a	
Thread D	irection:
Right-har	d
Thread L	ength:
Between	0.378 inches and 0.428 inches
Fastener	Length:
Between	0.638 inches and 0.668 inches
Head Sty	le:
Pan no. 2	
Head Dia	meter:
Between	0.477 inches and 0.492 inches
Head He	ght:
Between	0.140 inches and 0.150 inches
Grip Dia	neter:
Between	0.2485 inches and 0.2495 inches
Internal I	Drive Style:
Offset cru	ciform (torque set)
Thread D	iameter:
0.250 inc	nes
Grip Len	gth:
Between	0.240 inches and 0.260 inches
Thready	Qty Per Inch (tpi):
28	
Min. Ten	sile Strength (psi):
160000 p	ounds per square inch
Surface	Finish:
32.0 micr	pinches threads
Material:	
Iron alloy	660
Material	Specification:
Ams5731	assn standard single material response or ams5732 assn standard single material response or ams5737 a
material r	esponse
Surface [·]	Freatment:
Passivate	
Thread S	eries Designator:
Unjf	
Specifica	tion Data:
80205-na	s1578 professional/industrial association standard
Shelf Life	
N/a	
Linit Of N	leasure:

NSN 5305-01-260-8937

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

