Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-260-9807

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
0.142 inches	
Fastener Length:	
0.312 inches	
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.195 inches and	0.225 inches
First Diameter From Hea	d:
0.089 inches	
Distance From Largest B	earing Surface Of Head To End Of First Diameter:
Between 0.097 inches and	0.103 inches
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.112 inches	
Thready Qty Per Inch (tp	i):
40	
Min. Tensile Strength (ps	si):
80000 pounds per square	inch
Countersink Angle:	
Between 80.0 degrees and	1 82.0 degrees
Externally Relieved Body	/ Diameter Quantity:
1	
Material:	
Steel comp 301 or steel c	omp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or
steel comp 305 or steel co	omp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or
steel comp 316 or steel co	omp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel
comp 385	
Surface Treatment:	
Passivate	
Surface Treatment Speci	fication:
Qq-p-35 federal specificati	on single treatment response
Thread Series Designato	r:
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

## NSN 5305-01-260-9807

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

