

View Online at <https://aerobasegroup.com/nsn/5305-01-260-9822>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.183 inches and 0.250 inches

**Fastener Length:**

Between 0.219 inches and 0.250 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.124 inches and 0.140 inches

**Head Height:**

Between 0.070 inches and 0.083 inches

**Locking Feature:**

Patch threads

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.086 inches

**Thready Qty Per Inch (tpi):**

56

**Min. Tensile Strength (psi):**

60000 pounds per square inch

**Material:**

Steel comp 302 fastener or steel comp 304 fastener or steel comp 304l fastener or steel comp 305 fastener or steel comp 309 fastener or steel comp 310 fastener or steel comp 316 fastener or steel comp 316l fastener or steel comp 317 fastener or steel comp 321 fastener or steel comp 322 fastener or steel comp 324 fastener or steel comp 347 fastener

**Material Specification:**

Qq-s-763 federal specification all material responses fastener

**Surface Treatment:**

Passivate fastener

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0