

View Online at <https://aerobasegroup.com/nsn/5305-01-260-9826>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.313 inches and 0.375 inches

**Fastener Length:**

Between 0.720 inches and 0.750 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.389 inches and 0.414 inches

**Head Height:**

Between 0.161 inches and 0.170 inches

**Hole Diameter:**

0.062 inches

**Point Length:**

Between 0.345 inches and 0.375 inches

**Point Diameter:**

Between 0.120 inches and 0.125 inches

**Point Style:**

Flat

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

60000 pounds per square inch

**Hole Configuration Style:**

Round

**Criticality Code Justification:**

Feat

**Point Chamfer Angle:**

30.0 degrees

**Special Features:**

Item is f-16 landing gear specific

**Material:**

Steel comp 4140 or steel

**Material Specification:**

Mil-s-5626 military specification 1st material response or 66 federal standard 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 class 2 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.