

View Online at <https://aerobasegroup.com/nsn/5305-01-261-1900>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.306 inches and 0.326 inches

Fastener Length:

Between 1.119 inches and 1.139 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.499 inches and 0.507 inches

Grip Diameter:

Between 0.264 inches and 0.265 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.250 inches

Grip Length:

Between 0.803 inches and 0.823 inches

Thready Qty Per Inch (tpi):

28

Countersink Angle:

100.0 degrees

Special Features:

0.0156 in. Oversize shank for repair work only

Material:

Steel comp 4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Chromium

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.