

View Online at <https://aerobasegroup.com/nsn/5305-01-261-1905>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.308 inches and 0.338 inches

Fastener Length:

Between 1.183 inches and 1.213 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.338 inches and 0.381 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Internal Drive Style:

Tri-wing recess

Thread Diameter:

0.1900 inches

Grip Length:

Between 0.865 inches and 0.885 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response and mil-s-6049 military specification 2nd material response and ams6322 assn standard 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 ty2 cl 3 federal specification 1st treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas4403 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.