

View Online at <https://aerobasegroup.com/nsn/5305-01-261-1905>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.308 inches and 0.338 inches

**Fastener Length:**

Between 1.183 inches and 1.213 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.338 inches and 0.381 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Internal Drive Style:**

Tri-wing recess

**Thread Diameter:**

0.1900 inches

**Grip Length:**

Between 0.865 inches and 0.885 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response and mil-s-6049 military specification 2nd material response and ams6322 assn standard 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 cl 3 federal specification 1st treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas4403 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.