NSN 5305-01-261-6313

Shoulder Screw - Page 1 of 2

Thread Class:

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5305-01-261-6313

Right-hand
Thread Length:
Between 0.516 inches and 0.562 inches
Fastener Length:
Between 1.140 inches and 1.188 inches
Head Style:
Flat countersunk undercut
Head Diameter:
Between 0.575 inches and 0.633 inches
Head Height:
Between 0.061 inches and 0.064 inches
Shoulder Diameter:
0.327 inches first shoulder and 0.328 inches first shoulder
Shoulder Length:
0.533 inches first shoulder and 0.551 inches first shoulder
Internal Drive Style:
High-torque
Thread Diameter:
0.312 inches
Features Provided:
Cetyl alcohol lubricant and finished head
Thready Qty Per Inch (tpi):
24
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Shoulder Shape:
Round first shoulder
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Supplementary Features:
Hi-torque recess no. 5 ms33750; dbl shear str 14600 lb min; ts 6400 lb min; similar to nsn 5305-01-217-9063 except bolt only /w/o o-ring/
Thread Series Designator:
Unjf
Specification Data:
73197-ht4059 manufacturers standard
Shelf Life:
N/a

NSN 5305-01-261-6313 Shoulder Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

Demilitarization:

No

Fiig:

A003b0