NSN 5305-01-262-7873

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-262-7873 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.287 inches and 0.380 inches **Fastener Length:** Between 0.349 inches and 0.380 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas8102 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-262-7873

Machine Screw - Page 2 of 2



Fiig:

A500d0