

View Online at <https://aerobasegroup.com/nsn/5305-01-262-7885>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.352 inches and 0.403 inches

**Fastener Length:**

Between 2.164 inches and 2.184 inches

**Head Style:**

Crowned hexagon

**Head Height:**

Between 0.189 inches and 0.204 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Locking Feature:**

Detent ball grip

**Grip Diameter:**

Between 0.3737 inches and 0.3742 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.625 inches and 1.641 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

63000 pounds per square inch

**Hardness Rating:**

50.0 rockwell c locking feature and 62.0 rockwell c locking feature

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.036 inches first hole and 2.056 inches first hole

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel comp 631 spring or steel comp 302 spring

**Material Specification:**

Qq-s-763 federal specification single material response locking feature

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0