

View Online at <https://aerobasegroup.com/nsn/5305-01-262-8241>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.606 inches and 0.706 inches

**Fastener Length:**

Between 2.819 inches and 3.119 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.688 inches and 0.755 inches

**Grip Diameter:**

Between 0.4360 inches and 0.4370 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.437 inches

**Grip Length:**

Between 2.178 inches and 2.198 inches

**Thready Qty Per Inch (tpi):**

20

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Aluminum and chromate

**Surface Treatment Specification:**

Mil-c-83488, type 2, cl 3 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-83488 spec.