## NSN 5305-01-262-9016

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-262-9016

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.720 inches and 0.795 inches
Fastener Length:
Between 2.173 inches and 2.218 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.932 inches and 1.022 inches
Grip Diameter:
Between 0.495 inches and 0.499 inches
Internal Drive Style:
Cross recess type ii
Thread Diameter:
0.500 inches
Grip Length:
Between 1.423 inches and 1.453 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas517 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-01-262-9016

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

