NSN 5305-01-263-1676

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-263-1676 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.178 inches and 0.198 inches **Fastener Length:** Between 0.547 inches and 0.577 inches **Head Style:** Fillister **Head Diameter:** Between 0.167 inches and 0.177 inches **Head Height:** Between 0.092 inches and 0.122 inches **First Diameter From Head:** Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.302 inches and 0.322 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Qq-s-764 cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072 e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-01-263-1676

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.