

View Online at <https://aerobasegroup.com/nsn/5305-01-263-1683>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.323 inches

Fastener Length:

Between 0.496 inches and 0.526 inches

Head Style:

Pan no. 2

Head Diameter:

0.303 inches

Head Height:

0.040 inches

Grip Diameter:

Between 0.1881 inches and 0.1887 inches

Single Shear Strength:

95000 pounds per square inch

Internal Drive Style:

Tri-wing recess

Thread Diameter:

0.190 inches

Grip Length:

Between 0.178 inches and 0.198 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 assn standard single material response or mil-s-6049 assn standard single material response or ams6322 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 11, cl 2 assn standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas4703-3 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.