## NSN 5305-01-263-1683

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-263-1683

| Thread Class:  |            |
|--|------------|
| 3a   |            |
| Thread Direction:  |            |
| Right-hand   |            |
| Thread Length:   |            |
| 0.323 inches   |            |
| Fastener Length:   |            |
| Between 0.496 inches and 0.526 inches  |            |
| Head Style:  |            |
| Pan no. 2  |            |
| Head Diameter:   |            |
| 0.303 inches   |            |
| Head Height:   |            |
| 0.040 inches   |            |
| Grip Diameter:   |            |
| Between 0.1881 inches and 0.1887 inches  |            |
| Single Shear Strength:   |            |
| 95000 pounds per square inch   |            |
| Internal Drive Style:  |            |
| Tri-wing recess  |            |
| Thread Diameter:   |            |
| 0.190 inches   |            |
| Grip Length:   |            |
| Between 0.178 inches and 0.198 inches  |            |
| Thready Qty Per Inch (tpi):  |            |
| 32   |            |
| Min. Tensile Strength (psi):   |            |
| 160000 pounds per square inch  |            |
| Material:  |            |
| Steel comp 4340 or steel comp 8740   |            |
| Material Specification:  |            |
| Mil-s-5000 assn standard single material response or mil-s-6049 assn standard single material response or ams6322 assn stand | ard single |
| material response  |            |
| Surface Treatment:   |            |
| Cadmium  |            |
| Surface Treatment Specification:   |            |
| Qq-p-416, type 11, cl 2 assn standard single treatment response  |            |
| Thread Series Designator:  |            |
| Unjf   |            |
| Specification Data:  |            |
| 80205-nas4703-3 professional/industrial association specification  |            |
| Shelf Life:  |            |
| N/a  |            |

N/a

## NSN 5305-01-263-1683

Close Tolerance Screw - Page 2 of 2

AeroBase Group

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.