## NSN 5305-01-263-1686

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-263-1686 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.222 inches **Fastener Length:** Between 0.371 inches and 0.401 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.088 inches and 0.102 inches **Grip Diameter:** Between 0.1626 inches and 0.1636 inches Single Shear Strength: 95000 pounds per square inch **Internal Drive Style:** Tri-wing recess **Thread Diameter:** 0.164 inches **Grip Length:** Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Steel comp 3140 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 11, cl 2 assn standard single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas5002-1 professional/industrial association specification Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-263-1686

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0