## NSN 5305-01-263-6160

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-263-6160 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.338 inches and 0.388 inches **Fastener Length:** Between 0.660 inches and 0.690 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.258 inches and 0.305 inches **Grip Diameter:** Between 0.188 inches and 0.189 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Aluminum and chromate **Surface Treatment Specification:** Mil-c-83488 type 2, class 3 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5305-01-263-6160

Close Tolerance Screw - Page 2 of 2



ı	1	4	7	R.A		٠.	ıre	
ι	JIN		JI.	ıVΙ	чd	่อเ	ие	-

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.