NSN 5305-01-263-9990

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-263-9990 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.264 inches and 0.295 inches **Fastener Length:** Between 0.344 inches and 0.375 inches **Head Style:** Fillister **Head Diameter:** Between 0.208 inches and 0.226 inches **Head Height:** Between 0.111 inches and 0.132 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 88.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.215 inches and 0.225 inches **Primary Washer Style:** Flat internal teeth **Primary Washer Material Thickness:** Between 0.013 inches and 0.018 inches **Product Name:** Navy special project Material: Copper alloy 260 fastener or copper alloy 270 fastener or copper alloy 274 fastener **Material Specification:** Qq-w-321 comp 6, 7, 8 federal specification all material responses fastener **Surface Treatment:** Nickel primary washer **Thread Series Designator:** Unc Shelf Life:

She N/a

NSN 5305-01-263-9990

Assembled Washer Screw - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0