Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-263-9996

view Online at https://aerobasegroup.com/nsn/5305-01-263-9996
Thread Class:
За
Thread Direction:
Right-hand
Thread Length:
1.250 inches
Fastener Length:
Between 1.460 inches and 1.500 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.550 inches and 0.562 inches
Head Height:
Between 0.368 inches and 0.375 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
Between 0.3125 inches and 0.3160 inches
Thready Qty Per Inch (tpi):
24
24
24 Min. Tensile Strength (psi):
24 Min. Tensile Strength (psi): 160000 pounds per square inch
24 Min. Tensile Strength (psi): 160000 pounds per square inch Chamfer Angle:
24 <b>Min. Tensile Strength (psi):</b> 160000 pounds per square inch <b>Chamfer Angle:</b> Between 30.0 degrees and 45.0 degrees
24 Min. Tensile Strength (psi): 160000 pounds per square inch Chamfer Angle: Between 30.0 degrees and 45.0 degrees Material:
24 Min. Tensile Strength (psi): 160000 pounds per square inch Chamfer Angle: Between 30.0 degrees and 45.0 degrees Material: Iron alloy 660
24 Min. Tensile Strength (psi): 160000 pounds per square inch Chamfer Angle: Between 30.0 degrees and 45.0 degrees Material: Iron alloy 660 Material Specification:
24 Min. Tensile Strength (psi): 160000 pounds per square inch Chamfer Angle: Between 30.0 degrees and 45.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response
24 Min. Tensile Strength (psi): 160000 pounds per square inch Chamfer Angle: Between 30.0 degrees and 45.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment:
24 Min. Tensile Strength (psi): 160000 pounds per square inch Chamfer Angle: Between 30.0 degrees and 45.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate
24 Min. Tensile Strength (psi): 160000 pounds per square inch Chamfer Angle: Between 30.0 degrees and 45.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
24 Min. Tensile Strength (psi): 160000 pounds per square inch Chamfer Angle: Between 30.0 degrees and 45.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
24 Min. Tensile Strength (psi): 160000 pounds per square inch Chamfer Angle: Between 30.0 degrees and 45.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Carface Treatment Specification: Qq-p-35 federal specification single treatment response
24 Min. Tensile Strength (psi): 160000 pounds per square inch Chamfer Angle: Between 30.0 degrees and 45.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Inread Series Designator:
24 Min. Tensile Strength (psi): 160000 pounds per square inch Chamfer Angle: Between 30.0 degrees and 45.0 degrees Material: Ion alloy 660 Material Specification: Ans 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Aurface Treatment Specification: Qap-35 federal specification single treatment response Inread Series Designator: Unrf
24 Min. Tensile Strength (psi): 160000 pounds per square inch Chamfer Angle: Between 30.0 degrees and 45.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Passivate Marea Specification single treatment response Gurp-35 federal specification single treatment response Thread Series Designator: Unf Specification Data: B0205-nas1351 professional/industrial association standard

---

## NSN 5305-01-263-9996

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

