NSN 5305-01-264-0919

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-264-0919

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.090 inches and 1.250 inches
Fastener Length:
Between 1.190 inches and 1.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.735 inches and 0.750 inches
Head Height:
Between 0.449 inches and 0.500 inches
Locking Feature:
Strip threads or pellet threads or patch threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.500 inches
Width Across Flats:
Between 0.375 inches and 0.379 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b fastener
Chamfer Angle:
Between 30.0 degrees and 45.0 degrees
Material:
Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener
Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-01-264-0919

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0