

View Online at <https://aerobasegroup.com/nsn/5305-01-264-1148>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.195 inches and 0.255 inches

**Fastener Length:**

Between 0.245 inches and 0.255 inches

**Head Style:**

Watertight

**Head Diameter:**

Between 0.201 inches and 0.213 inches

**Head Height:**

Between 0.051 inches and 0.059 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.112 inches

**Width Across Flats:**

0.063 inches

**Thready Qty Per Inch (tpi):**

40

**Special Features:**

Supplied with o-ring

**Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303 plus x or steel comp 303cu or steel comp 303f or steel comp 303ma or steel comp 303se or steel comp 304 or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 or steel comp 304l

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0