NSN 5305-01-264-1451

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-264-1451 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** Between 0.735 inches and 0.764 inches **Head Style:** Knurled no. 2 **Head Diameter:** Between 0.610 inches and 0.640 inches **Head Height:** 0.249 inches Point Length: Between 0.110 inches and 0.140 inches **Point Diameter:** Between 0.120 inches and 0.130 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.375 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** Between 55.0 degrees and 65.0 degrees Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5305-01-264-1451

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0