## NSN 5305-01-264-1462

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-264-1462

| Thread Class:   |
|---|
| 2a  |
| Thread Direction:                                       |
| Right-hand  |
| Thread Length:  |
| 0.940 inches  |
| Fastener Length:  |
| Between 1.780 inches and 1.860 inches                   |
| Head Style:   |
| Flat extended washer                                    |
| Head Diameter:  |
| 0.750 inches  |
| Head Height:  |
| 0.820 inches  |
| Extended Washer Diameter:                               |
| 1.500 inches  |
| Extended Washer Thickness:                              |
| 0.120 inches  |
| Point Style:  |
| Flat  |
| Thread Diameter:  |
| 0.190 inches  |
| Thready Qty Per Inch (tpi):                             |
| 32  |
| Product Name:   |
| Navy special project                                    |
| Special Features:                                       |
| Extended washer raised diamond knurled                  |
| Material:   |
| Steel comp 303  |
| Material Specification:                                 |
| Astm a582 assn standard single material response        |
| Surface Treatment:                                      |
| Passivate   |
| Surface Treatment Specification:                        |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator:                               |
| Unf   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

## NSN 5305-01-264-1462

Thumbscrew - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0