

View Online at <https://aerobasegroup.com/nsn/5305-01-264-3206>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.223 inches

**Fastener Length:**

Between 0.673 inches and 0.703 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

0.331 inches

**Head Height:**

0.072 inches

**Grip Diameter:**

Between 0.1621 inches and 0.1627 inches

**Single Shear Strength:**

95000 pounds per square inch

**Internal Drive Style:**

Tri-wing recess

**Thread Diameter:**

0.164 inches

**Grip Length:**

Between 0.365 inches and 0.385 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Material:**

Steel comp 4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 assn standard single material response or mil-s-6049 assn standard single material response or ams6322 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416a, type 11, cl 3 assn standard single treatment response

**Thread Series Designator:**

Unjc

**Specification Data:**

80205-nas4402-6 professional/industrial association specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.