Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-264-4199

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
0.250 inches	
Fastener Length:	
Between 0.594 inches and 0.6	25 inches
Head Style:	
Pan	
Head Diameter:	
Between 0.208 inches and 0.2	26 inches
Head Height:	
Between 0.087 inches and 0.0	97 inches
First Diameter From Head:	
0.095 inches	
Distance From Largest Bear	ng Surface Of Head To End Of First Diameter:
0.375 inches	
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.138 inches	
Thready Qty Per Inch (tpi):	
32	
Externally Relieved Body Dia	Imeter Quantity:
1	
Material:	
Steel comp 301 or steel comp	302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or
steel comp 305 or steel comp	308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or
	316I or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel
comp 385	
Material Specification:	
	all material responses or 66 federal standard all material responses
Surface Treatment:	
Passivate	
Surface Treatment Specifica	
Qq-p-35 federal specification s	ingle treatment response
Thread Series Designator:	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	

NSN 5305-01-264-4199

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

