## NSN 5305-01-264-4510



Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-264-4510 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.319 inches and 0.350 inches Fastener Length: Between 0.719 inches and 0.750 inches **Head Style:** Pan **Head Diameter:** Between 0.155 inches and 0.167 inches **Head Height:** Between 0.053 inches and 0.062 inches First Diameter From Head: 0.060 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.400 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 348 or steel comp 384 or steel comp comp 385 **Material Specification:** Qq-s-763 federal specification all material responses or 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

**Unit Of Measure:** 

Demilitarization:

N/a

## NSN 5305-01-264-4510

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0