## NSN 5305-01-264-4516

Between 0.183 inches and 0.250 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

За

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-264-4516

Detween 6.166 menes and 6.266 menes
Fastener Length:
Between 0.219 inches and 0.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.136 inches and 0.140 inches
Head Height:
Between 0.044 inches and 0.053 inches
Locking Feature:
Patch threads
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.086 inches
Thready Qty Per Inch (tpi):
56
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
24.0 rockwell c and 35.0 rockwell c
Minimum Yield Strength:
85000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1191 professional/industrial association standard

## NSN 5305-01-264-4516

Socket Head Cap Screw - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0