

View Online at <https://aerobasegroup.com/nsn/5305-01-264-5836>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

2.030 inches

Head Style:

Hexagon

Head Height:

0.193 inches

Width Between Flats:

0.375 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.190 inches

Width Across Flats:

0.156 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Special Features:

Furnish with stop nut a-286 cres per ams 5731, passivate per qq-p-35, 140000 p.S.I. Min ams5529; coil spring 18-8 type 302 cres per astm a580, passivate; spring cup 18-8 type 300 cres per astm-a-555, astm-a-581 ams 5640; disc spring 17-7 ph cres per ams 5529, 240000 p.S.I. Min per ams 5529, passivate; also contains self-locking slug round per mil-f-18240

Material:

Steel comp 301 stand-off or steel comp 302 stand-off or steel comp 304 stand-off or steel comp 316 stand-off or steel comp 303 plus x stand-off or steel comp 303se stand-off or steel comp 303pb stand-off

Material Specification:

Mil-s-5059 military specification single material response primary washer

Surface Treatment:

Passivate stand-off

Surface Treatment Specification:

Qq-p-416 type 1 cl 2 federal specification single treatment response fastener

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.